

SP-4008

Scope Mount Ø34 H44mm/1.73" OMIL PIC

Picatinny mount for use with NV Equipment

Rings: 34 mm

Tilt: 0 MIL/MOA Height: 44 mm/1.73" Length: 121 mm/4.76"

Interfaces: 7 sets

Weight:

EAN: 7340150700232

265 q/9.3 oz

The IDEAL SCOPE MOUNT SYSTEM series of mounts feature seven set of interfaces to attach any of more than 40 different accessories, and has a bubble level integrated in the rear plane of the mount body to prevent canting of the rifle. The rings are diagonally cut for increased

32 mm/1.26" 57 mm/2.24"

44 mm/1.73"

visibility of the elevation and windage turrets (US Patent 8,733,011).

The mounts are machined from billet 7075 T651 aluminum and all aluminum parts are hardcoat anodized. The Torx 20 ring and clamping screws are zinc-nickel coated for corrosion resistance. The screws come pre-waxed from the factory to ensure proper torque values.

The mount is shipped with a manual and a "wedge" leveling key.

NOTE:

The SP-4008 is designed for use on rifles with MIL-STD-1913 or STANAG 4694 rails together with high clip-on NV attachments such as the NSV-80. The SP-4008 will fit most 34 mm scope tubes except for scopes with extended erector housings, such as the US Optics TPAL/EREK and the Nightforce BEAST.

Spuhr i Dalby AB

Phone: +46 46 712 012 Address: Terminalvägen 19

Web: www.spuhr.com SE-246 42 Löddeköpinge

Sweden