

K624i

PROFESSIONAL CHOICE FOR LONG DISTANCES



The K624i sets standards in handling and ergonomics thanks to the unique arrangement of its operating elements. It offers outstanding optical performance, mechanical perfection and a unique range of well proven reticles for professionals and competition shooters.

PRODUCT HIGHLIGHTS

- Wide field of view, exceptionally comfortable eyepiece and high contrast image
- Precise, clearly defined click mechanism and reliable repeat accuracy
- Optional left or right side windage
- Parallax wheel integrated into the elevation turret (patented) (50 m to ∞)
- Precise illuminated reticles in 1st focal plane

TECHNICAL DATA

Magnification:	6 - 24
Objective lens diameter:	56 mm
Exit pupil:	9.4 - 2.3 mm
Eye relief:	90 mm
Field of view:	6.8 - 1.7 m/100 m
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	18.3 - 36.7
Impact correction per click:	.1 MRAD ¼ MOA
Adjustment range (E/W):	2.5 / 1.1 m/100 m
Parallax adjustment:	50 m till ∞
Tube diameter:	34 mm
Length:	405 mm
Weight:	950 g
Focal plane:	1
Illuminated:	Yes
Warranty:	10 years

FEATURES




1st focal plane



Main tube 34 mm



Adjustment direction CW
or CCW



Windage left or right




Zero Stop




MIL


RETICLES / SUBTENSIONS




MSR/Ki



Mil3



Mil4



SKMR4